Northfork Machine Dishwashing Powder

ACCO Brands New Zealand Limited
Version No: **1.4**
Safety Data Sheet according to HSNO Regulations

Issue Date: 20/09/2024

S.GHS.NZL.EN

SECTION 1 IDENTIFICATION OF THE SUBSTANCE / MIXTURE AND OF THE COMPANY / UNDERTAKING

Product Identifier

Product name	Northfork Machine Dishwashing Powder
Synonyms	Not Available
Proper shipping name	CORROSIVE SOLID, N.O.S.
Other means of identification	5kg - 631031400, 10kg - 631031600

Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses	Detergent for machine dishwashers

Details of the supplier of the safety data sheet

Registered company name	**ACCO Brands New Zealand Limited**
Address	29 Pukekiwiriki Pl, Highbrook Business Park, East Tamaki, Auckland 2013
Telephone	+64 9 633 2288
Fax	+64 9 636 7272 / 0800 500 526
Website	www.accobrands.co.nz
Email	sds.anz@acco.com

Emergency telephone number

Association / Organisation	**National Poisons Centre**
Emergency telephone numbers	0800 764 766
Other emergency telephone numbers	0800 764 766

SECTION 2 HAZARDS IDENTIFICATION

Classification of the substance or mixture

Classification [1]	Metal Corrosion Category 1, Skin Corrosion/Irritation Category 1B, Serious Eye Damage Category 1, Acute Aquatic Hazard Category 3, Chronic Aquatic Hazard Category 3
Legend:	*1. Classified by Chemwatch; 2. Classification drawn from CCID EPA NZ; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI*
Determined by Chemwatch using GHS/HSNO criteria	8.1A, 8.2B, 8.3A, 9.1C, 9.1D

Label elements

Hazard pictogram(s)	
SIGNAL WORD	**DANGER**

Hazard statement(s)

H290	May be corrosive to metals.
H314	Causes severe skin burns and eye damage.
H412	Harmful to aquatic life with long lasting effects.

Precautionary statement(s) General

P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P103	Read label before use.

Precautionary statement(s) Prevention

P260	Do not breathe dust/fume/gas/mist/vapours/spray.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P234	Keep only in original packaging.

Continued...

P273	Avoid release to the environment.

Precautionary statement(s) Response

P301+P330+P331	IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310	Immediately call a POISON CENTER/doctor/physician/first aider.
P321	Specific treatment (see advice on this label).
P363	Wash contaminated clothing before reuse.
P390	Absorb spillage to prevent material damage.
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Precautionary statement(s) Storage

P405	Store locked up.

Precautionary statement(s) Disposal

P501	Dispose of contents/container in accordance with local regulations.

SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS

Substances

See section below for composition of Mixtures

Mixtures

CAS No	%[weight]	Name
497-19-8	30-60%	sodium carbonate
7758-29-4	10-30%	sodium tripolyphosphate
9003-11-6	<10%	polypropylene/ polyethylene glycol copolymer
6834-92-0	30-60%	sodium metasilicate, anhydrous
2893-78-9	<10%	sodium dichloroisocyanurate

SECTION 4 FIRST AID MEASURES

Description of first aid measures

Eye Contact	If this product comes in contact with the eyes: ▸ Immediately hold eyelids apart and flush the eye continuously with running water. ▸ Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids. ▸ Continue flushing until advised to stop by the Poisons Information Centre or a doctor, or for at least 15 minutes. ▸ Transport to hospital or doctor without delay. ▸ Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.
Skin Contact	If skin or hair contact occurs: ▸ Immediately flush body and clothes with large amounts of water, using safety shower if available. ▸ Quickly remove all contaminated clothing, including footwear. ▸ Wash skin and hair with running water. Continue flushing with water until advised to stop by the Poisons Information Centre. ▸ Transport to hospital, or doctor.
Inhalation	▸ If fumes or combustion products are inhaled remove from contaminated area. ▸ Lay patient down. Keep warm and rested. ▸ Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures. ▸ Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary. ▸ Transport to hospital, or doctor, without delay. ▸ Inhalation of vapours or aerosols (mists, fumes) may cause lung oedema. ▸ Corrosive substances may cause lung damage (e.g. lung oedema, fluid in the lungs). ▸ As this reaction may be delayed up to 24 hours after exposure, affected individuals need complete rest (preferably in semi-recumbent posture) and must be kept under medical observation even if no symptoms are (yet) manifested. ▸ Before any such manifestation, the administration of a spray containing a dexamethasone derivative or beclomethasone derivative may be considered. **This must definitely be left to a doctor or person authorised by him/her.** (ICSC13719)
Ingestion	▸ For advice, contact a Poisons Information Centre or a doctor at once. ▸ Urgent hospital treatment is likely to be needed. ▸ If swallowed do **NOT** induce vomiting. ▸ If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration. ▸ Observe the patient carefully. ▸ Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious. ▸ Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink. ▸ Transport to hospital or doctor without delay.

Indication of any immediate medical attention and special treatment needed

Continued...

For acute or short-term repeated exposures to highly alkaline materials:
- Respiratory stress is uncommon but present occasionally because of soft tissue edema.
- Unless endotracheal intubation can be accomplished under direct vision, cricothyroidotomy or tracheotomy may be necessary.
- Oxygen is given as indicated.
- The presence of shock suggests perforation and mandates an intravenous line and fluid administration.
- Damage due to alkaline corrosives occurs by liquefaction necrosis whereby the saponification of fats and solubilisation of proteins allow deep penetration into the tissue.

Alkalis continue to cause damage after exposure.
INGESTION:
- Milk and water are the preferred diluents

No more than 2 glasses of water should be given to an adult.
- Neutralising agents should never be given since exothermic heat reaction may compound injury.

* Catharsis and emesis are absolutely contra-indicated.
* Activated charcoal does not absorb alkali.
* Gastric lavage should not be used.

Supportive care involves the following:
- Withhold oral feedings initially.
- If endoscopy confirms transmucosal injury start steroids only within the first 48 hours.
- Carefully evaluate the amount of tissue necrosis before assessing the need for surgical intervention.
- Patients should be instructed to seek medical attention whenever they develop difficulty in swallowing (dysphagia).

SKIN AND EYE:
- Injury should be irrigated for 20-30 minutes.

Eye injuries require saline. [Ellenhorn & Barceloux: Medical Toxicology]

SECTION 5 FIREFIGHTING MEASURES

Extinguishing media

- Water spray or fog.
- Foam.
- Dry chemical powder.
- BCF (where regulations permit).
- Carbon dioxide.

Special hazards arising from the substrate or mixture

Fire Incompatibility	▸ Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result

Advice for firefighters

Fire Fighting	▸ Alert Fire Brigade and tell them location and nature of hazard. ▸ Wear full body protective clothing with breathing apparatus. ▸ Prevent, by any means available, spillage from entering drains or water course. ▸ Use fire fighting procedures suitable for surrounding area. ▸ **Do not** approach containers suspected to be hot. ▸ Cool fire exposed containers with water spray from a protected location. ▸ If safe to do so, remove containers from path of fire. ▸ Equipment should be thoroughly decontaminated after use.
Fire/Explosion Hazard	Combustible. Will burn if ignited. Combustion products include: carbon monoxide (CO) carbon dioxide (CO2) phosphorus oxides (POx) silicon dioxide (SiO2) other pyrolysis products typical of burning organic material. May emit corrosive fumes.

SECTION 6 ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

See section 8

Environmental precautions

See section 12

Methods and material for containment and cleaning up

Minor Spills	Environmental hazard - contain spillage. ▸ Remove all ignition sources. ▸ Clean up all spills immediately. ▸ Avoid contact with skin and eyes. ▸ Control personal contact with the substance, by using protective equipment. ▸ Use dry clean up procedures and avoid generating dust. ▸ Place in a suitable, labelled container for waste disposal. ▸ Drains for storage or use areas should have retention basins for pH adjustments and dilution of spills before discharge or disposal of material. ▸ Check regularly for spills and leaks.
Major Spills	Environmental hazard - contain spillage. ▸ Clear area of personnel and move upwind. ▸ Alert Fire Brigade and tell them location and nature of hazard. ▸ Wear full body protective clothing with breathing apparatus. ▸ Prevent, by any means available, spillage from entering drains or water course. ▸ Consider evacuation (or protect in place).

Continued...

	▸ Stop leak if safe to do so. ▸ Contain spill with sand, earth or vermiculite. ▸ Collect recoverable product into labelled containers for recycling.

Personal Protective Equipment advice is contained in Section 8 of the SDS.

SECTION 7 HANDLING AND STORAGE

Precautions for safe handling

Safe handling	▸ Avoid all personal contact, including inhalation. ▸ Wear protective clothing when risk of exposure occurs. ▸ Use in a well-ventilated area. ▸ **WARNING:** To avoid violent reaction, **ALWAYS** add material to water and **NEVER** water to material. ▸ Avoid smoking, naked lights or ignition sources. ▸ Avoid contact with incompatible materials. ▸ When handling, **DO NOT** eat, drink or smoke. ▸ Keep containers securely sealed when not in use.
Other information	▸ Store in original containers. ▸ Keep containers securely sealed. ▸ Store in a cool, dry, well-ventilated area. ▸ Store away from incompatible materials and foodstuff containers. ▸ Protect containers against physical damage and check regularly for leaks. ▸ Observe manufacturer's storage and handling recommendations contained within this SDS. ▸ **DO NOT** store near acids, or oxidising agents ▸ No smoking, naked lights, heat or ignition sources.

Conditions for safe storage, including any incompatibilities

Suitable container	▸ **DO NOT** use aluminium or galvanised containers ▸ Lined metal can, lined metal pail/ can. ▸ Plastic pail. ▸ Polyliner drum. ▸ Packing as recommended by manufacturer. ▸ Check all containers are clearly labelled and free from leaks. For low viscosity materials ▸ Drums and jerricans must be of the non-removable head type. ▸ Where a can is to be used as an inner package, the can must have a screwed enclosure. For materials with a viscosity of at least 2680 cSt. (23 deg. C) and solids (between 15 C deg. and 40 deg C.): ▸ Removable head packaging; ▸ Cans with friction closures and ▸ low pressure tubes and cartridges may be used. - Where combination packages are used, and the inner packages are of glass, porcelain or stoneware, there must be sufficient inert cushioning material in contact with inner and outer packages unless the outer packaging is a close fitting moulded plastic box and the substances are not incompatible with the plastic.
Storage incompatibility	Sodium carbonate: ▸ aqueous solutions are strong bases ▸ reacts violently with finely divided aluminium, fluorine, lithium, phosphorus pentoxide, sulfuric acid ▸ reacts with fluorine gas at room temperature, generating incandescence. ▸ is incompatible with organic anhydrides, acrylates, alcohols, aldehydes, alkylene oxides, substituted allyls, cellulose nitrate, cresols, caprolactam solution, epichlorohydrin, ethylene dichloride, isocyanates, ketones, glycols, nitrates, phenols, phosphorus pentoxide 2,4,6-trinitrotoluene ▸ forms explosive material with 2,4,5-trinitrotoluene and increases the thermal sensitivity of 2,4,6-trinitrotoluene (TNT) by decreasing the temperature of explosion from 297 deg. C to 218 deg. C ▸ attacks metal. ▸ In presence of moisture, the material is corrosive to aluminium, zinc and tin producing highly flammable hydrogen gas. ▸ Phosphates are incompatible with oxidising and reducing agents. ▸ Phosphates are susceptible to formation of highly toxic and flammable phosphine gas in the presence of strong reducing agents such as hydrides. ▸ Partial oxidation of phosphates by oxidizing agents may result in the release of toxic phosphorus oxides. ▸ Avoid oxidising agents, acids, acid chlorides, acid anhydrides, chloroformates. ▸ Avoid contact with copper, aluminium and their alloys. Avoid storage of dichloroisocyanurates with ammonia, urea or similar nitrogen containing compounds, inorganic reducing compounds, calcium hypochlorite, alkalis and water. Corrosive to most metals in the presence of moisture. ▸ Many compounds containing more than one N-halogen bond are unstable and exhibit explosive properties. BRETHERICK L.: Handbook of Reactive Chemical Hazards ▸ Contact with acids produces toxic fumes ▸ Avoid strong bases.

SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION

Control parameters

OCCUPATIONAL EXPOSURE LIMITS (OEL)

INGREDIENT DATA

Not Available

EMERGENCY LIMITS

Ingredient	Material name	TEEL-1	TEEL-2	TEEL-3
sodium carbonate	Sodium carbonate	7.6 mg/m3	83 mg/m3	500 mg/m3

Continued...

sodium tripolyphosphate	Sodium tripolyphosphate	0.61 mg/m3	6.8 mg/m3	620 mg/m3
polypropylene/ polyethylene glycol copolymer	Polypropylene-polyethylene glycol; (Pluronic L-81)	6.9 mg/m3	76 mg/m3	460 mg/m3
sodium metasilicate, anhydrous	Sodium metasilicate pentahydrate	6.6 mg/m3	73 mg/m3	440 mg/m3
sodium metasilicate, anhydrous	Sodium silicate; (Sodium metasilicate)	3.8 mg/m3	42 mg/m3	250 mg/m3

Ingredient	Original IDLH	Revised IDLH
sodium carbonate	Not Available	Not Available
sodium tripolyphosphate	Not Available	Not Available
polypropylene/ polyethylene glycol copolymer	Not Available	Not Available
sodium metasilicate, anhydrous	Not Available	Not Available
sodium dichloroisocyanurate	Not Available	Not Available

Exposure controls

Appropriate engineering controls	Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection. The basic types of engineering controls are: Process controls which involve changing the way a job activity or process is done to reduce the risk. Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment. Ventilation can remove or dilute an air contaminant if designed properly. The design of a ventilation system must match the particular process and chemical or contaminant in use. Employers may need to use multiple types of controls to prevent employee overexposure. Local exhaust ventilation usually required.
Personal protection	
Eye and face protection	▸ Safety glasses with unperforated side shields may be used where continuous eye protection is desirable, as in laboratories; spectacles are not sufficient where complete eye protection is needed such as when handling bulk-quantities, where there is a danger of splashing, or if the material may be under pressure. ▸ Chemical goggles.whenever there is a danger of the material coming in contact with the eyes; goggles must be properly fitted. ▸ Full face shield (20 cm, 8 in minimum) may be required for supplementary but never for primary protection of eyes; these afford face protection. ▸ Alternatively a gas mask may replace splash goggles and face shields. ▸ Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available.
Skin protection	See Hand protection below
Hands/feet protection	▸ Elbow length PVC gloves
Body protection	See Other protection below
Other protection	▸ Overalls. ▸ PVC Apron. ▸ PVC protective suit may be required if exposure severe. ▸ Eyewash unit. ▸ Ensure there is ready access to a safety shower.

Recommended material(s)

GLOVE SELECTION INDEX

Glove selection is based on a modified presentation of the:
"Forsberg Clothing Performance Index".
The effect(s) of the following substance(s) are taken into account in the ***computer-generated*** selection:
Machine Dishwashing Powder

Material	CPI
NATURAL RUBBER	A
NITRILE	A

* CPI - Chemwatch Performance Index
A: Best Selection
B: Satisfactory; may degrade after 4 hours continuous immersion
C: Poor to Dangerous Choice for other than short term immersion
NOTE: As a series of factors will influence the actual performance of the glove, a final selection must be based on detailed observation. -
* Where the glove is to be used on a short term, casual or infrequent basis, factors such as "feel" or convenience (e.g. disposability), might dictate a choice of gloves which might otherwise be unsuitable following long-term or frequent use. A qualified practitioner should be consulted.

Respiratory protection

Type AB-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Continued...

Selection of the Class and Type of respirator will depend upon the level of breathing zone contaminant and the chemical nature of the contaminant. Protection Factors (defined as the ratio of contaminant outside and inside the mask) may also be important.

Required minimum protection factor	Maximum gas/vapour concentration present in air p.p.m. (by volume)	Half-face Respirator	Full-Face Respirator
up to 10	1000	AB-AUS / Class1 P2	-
up to 50	1000	-	AB-AUS / Class 1 P2
up to 50	5000	Airline *	-
up to 100	5000	-	AB-2 P2
up to 100	10000	-	AB-3 P2
100+			Airline**

*** - Continuous Flow ** - Continuous-flow or positive pressure demand**
A(All classes) = Organic vapours, B AUS or B1 = Acid gasses, B2 = Acid gas or hydrogen cyanide(HCN), B3 = Acid gas or hydrogen cyanide(HCN), E = Sulfur dioxide(SO2), G = Agricultural chemicals, K = Ammonia(NH3), Hg = Mercury, NO = Oxides of nitrogen, MB = Methyl bromide, AX = Low boiling point organic compounds(below 65 degC)

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Appearance	A white powder with blue beads

Physical state	Solid	**Relative density (Water = 1)**	1.00
Odour	Not Available	**Partition coefficient n-octanol / water**	Not Available
Odour threshold	Not Available	**Auto-ignition temperature (°C)**	Not Available
pH (as supplied)	Not Available	**Decomposition temperature**	Not Available
Melting point / freezing point (°C)	Not Available	**Viscosity (cSt)**	Not Available
Initial boiling point and boiling range (°C)	Not Available	**Molecular weight (g/mol)**	Not Available
Flash point (°C)	Not Available	**Taste**	Not Available
Evaporation rate	Not Available	**Explosive properties**	Not Available
Flammability	Not Available	**Oxidising properties**	Not Available
Upper Explosive Limit (%)	Not Available	**Surface Tension (dyn/cm or mN/m)**	Not Applicable
Lower Explosive Limit (%)	Not Available	**Volatile Component (%vol)**	Not Available
Vapour pressure (kPa)	Not Available	**Gas group**	Not Available
Solubility in water	Miscible	**pH as a solution (1%)**	11-13
Vapour density (Air = 1)	Not Available	**VOC g/L**	Not Available

SECTION 10 STABILITY AND REACTIVITY

Reactivity	See section 7
Chemical stability	▸ Unstable in the presence of incompatible materials. ▸ Product is considered stable. ▸ Hazardous polymerisation will not occur.
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

SECTION 11 TOXICOLOGICAL INFORMATION

Information on toxicological effects

Inhaled	The material can cause respiratory irritation in some persons. The body's response to such irritation can cause further lung damage. Inhaling corrosive bases may irritate the respiratory tract. Symptoms include cough, choking, pain and damage to the mucous membrane. Chlorine vapour is extremely irritating to the airways and lungs, causing coughing, choking, breathing difficulty, chest pain, headache, vomiting, fluid accumulation in the lungs, chest infection and loss of consciousness. Effects may be delayed. Long term exposure (at workplace) may lead to corrosion of the teeth, irritate the linings of the nose and may increase the likelihood of developing tuberculosis. Recent studies have not confirmed these findings. Very low concentrations may irritate the eyes, nose and throat and cause the above reactions.

Continued...

	Inhalation of sodium carbonate may cause coughing, sore throat, difficulty breathing. Fluid accumulation in the lungs can occur with exposure to high doses or over a long period of time.
Ingestion	Ingestion of alkaline corrosives may produce burns around the mouth, ulcerations and swellings of the mucous membranes, profuse saliva production, with an inability to speak or swallow. Both the oesophagus and stomach may experience burning pain; vomiting and diarrhoea may follow. Accidental ingestion of the material may be damaging to the health of the individual. Inorganic polyphosphates are used extensively in domestic and industrial products. Experiments on rats showed kidney damage, growth retardation, and tetany due to low calcium. Oral intake of dichloroisocyanurates is corrosive to the mouth, gullet and internal organs, depending on the concentration and may result in weakness, lethargy, tremors, salivation, excessive secretion of tears and possible coma. Its toxicity seems to be mainly related to the corrosive effect on the stomach lining. Severity of symptoms seems to be more related to concentration than amount swallowed. As absorption of phosphates from the bowel is poor, poisoning this way is less likely. Effects can include vomiting, tiredness, fever, diarrhoea, low blood pressure, slow pulse, cyanosis, spasms of the wrist, coma and severe body spasms.
Skin Contact	The material can produce severe chemical burns following direct contact with the skin. Skin contact is not thought to have harmful health effects (as classified under EC Directives); the material may still produce health damage following entry through wounds, lesions or abrasions. Skin contact with alkaline corrosives may produce severe pain and burns; brownish stains may develop. The corroded area may be soft, gelatinous and necrotic; tissue destruction may be deep. Contact with concentrated solutions of sodium carbonate may cause tissue damage - "soda ulcers". Open cuts, abraded or irritated skin should not be exposed to this material Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.
Eye	If applied to the eyes, this material causes severe eye damage. Direct eye contact with corrosive bases can cause pain and burns. There may be swelling, epithelium destruction, clouding of the cornea and inflammation of the iris. Mild cases often resolve; severe cases can be prolonged with complications such as persistent swelling, scarring, permanent cloudiness, bulging of the eye, cataracts, eyelids glued to the eyeball and blindness. 510sodacarb
Chronic	Repeated or prolonged exposure to corrosives may result in the erosion of teeth, inflammatory and ulcerative changes in the mouth and necrosis (rarely) of the jaw. Bronchial irritation, with cough, and frequent attacks of bronchial pneumonia may ensue. Long-term exposure to respiratory irritants may result in airways disease, involving difficulty breathing and related whole-body problems. Substance accumulation, in the human body, may occur and may cause some concern following repeated or long-term occupational exposure. The chlorinated isocyanurates have low acute manifestation. It irritates the eyes and skin but is not considered to be skin sensitizers. Studies show that it does not cause cancer or foetal toxicity on acute exposure. However, on chronic inhalation and ingestion exposure, it produces toxicity involving organ damage, breathing difficulty, headaches and possibly reproductive and foetal toxicity. Long term inhalation of sodium carbonate may result in nose damage and lung disease. Sodium phosphate dibasic can cause stones in the kidney, loss of mineral from the bones and loss of thyroid gland function. In long-term animal studies, inorganic polyphosphates produced growth inhibition, increased kidney weights, bone decalcification, enlargement of the parathyroid gland, inorganic phosphate in the urine, focal necrosis of the kidney and alterations of muscle fibre size. Inorganic phosphates have not been shown to cause cancer, genetic damage or reproductive or developmental damage in animal tests.

Machine Dishwashing Powder	**TOXICITY**	**IRRITATION**
	Not Available	Not Available
sodium carbonate	**TOXICITY**	**IRRITATION**
	dermal (rat) LD50: >2000 mg/kg[2]	Eye (rabbit): 100 mg/24h moderate
	Inhalation (guinea pig) LC50: 0.4 mg/l/2h[2]	Eye (rabbit): 100 mg/30s mild
	Oral (rat) LD50: 2800 mg/kg[2]	Eye (rabbit): 50 mg SEVERE
		Eye: adverse effect observed (irritating)[1]
		Skin (rabbit): 500 mg/24h mild
		Skin: no adverse effect observed (not irritating)[1]
sodium tripolyphosphate	**TOXICITY**	**IRRITATION**
	Dermal (rabbit) LD50: >3160 mg/kg[2]	Not Available
	Oral (rat) LD50: >2000 mg/kg[1]	
polypropylene/ polyethylene glycol copolymer	**TOXICITY**	**IRRITATION**
	Inhalation (rat) LC50: 0.32 mg/l/4H[2]	Eye (rabbit): 500 mg/24h - mild
	Oral (rat) LD50: 2300 mg/kg[2]	Skin (rabbit): 500 mg/24h - mild
sodium metasilicate, anhydrous	**TOXICITY**	**IRRITATION**
	dermal (rat) LD50: >5000 mg/kg[1]	Skin (human): 250 mg/24h SEVERE
	Oral (rat) LD50: =600 mg/kg[2]	Skin (rabbit): 250 mg/24h SEVERE
sodium dichloroisocyanurate	**TOXICITY**	**IRRITATION**
	dermal (rat) LD50: >5000 mg/kg[2]	Eye (rabbit): 10 mg/24hr-moderate
	Inhalation (rat) LC50: 73.16642175 mg/l/1hour[2]	Skin (rabbit) : Severe *
	Oral (rat) LD50: 700 mg/kg[2]	

Continued...

Legend:	*1. Value obtained from Europe ECHA Registered Substances - Acute toxicity 2.* Value obtained from manufacturer's SDS. Unless otherwise specified data extracted from RTECS - Register of Toxic Effect of chemical Substances*

POLYPROPYLENE/ POLYETHYLENE GLYCOL COPOLYMER	The material may be irritating to the eye, with prolonged contact causing inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis. * Varies - dependent on degree of ethoxylation.
SODIUM DICHLOROISOCYANURATE	Dermal (rabbit) LD50: 3160-5100 mg/kg * Manufacturer The material may produce moderate eye irritation leading to inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis.
Machine Dishwashing Powder & SODIUM CARBONATE & SODIUM TRIPOLYPHOSPHATE & SODIUM METASILICATE, ANHYDROUS & SODIUM DICHLOROISOCYANURATE	Asthma-like symptoms may continue for months or even years after exposure to the material ends. This may be due to a non-allergic condition known as reactive airways dysfunction syndrome (RADS) which can occur after exposure to high levels of highly irritating compound. Main criteria for diagnosing RADS include the absence of previous airways disease in a non-atopic individual, with sudden onset of persistent asthma-like symptoms within minutes to hours of a documented exposure to the irritant. Other criteria for diagnosis of RADS include a reversible airflow pattern on lung function tests, moderate to severe bronchial hyperreactivity on methacholine challenge testing, and the lack of minimal lymphocytic inflammation, without eosinophilia. RADS (or asthma) following an irritating inhalation is an infrequent disorder with rates related to the concentration of and duration of exposure to the irritating substance. On the other hand, industrial bronchitis is a disorder that occurs as a result of exposure due to high concentrations of irritating substance (often particles) and is completely reversible after exposure ceases. The disorder is characterized by difficulty breathing, cough and mucus production.
Machine Dishwashing Powder & SODIUM CARBONATE	For sodium carbonate: Sodium carbonate has little potential for skin irritation, but is irritating to the eyes. Due to its alkaline properties, irritation of the airways is also possible. There is no data available for animal studies regarding the repeated dose toxicity of sodium carbonate by any route. There is no evidence that sodium carbonate causes whole-body effects under normal handling and use. Sodium carbonate does not reach the foetus or the reproductive organs, which shows that there is no risk for developmental or reproductive toxicity. Sodium carbonate has not been shown to cause genetic toxicity or mutations.
Machine Dishwashing Powder & SODIUM METASILICATE, ANHYDROUS & SODIUM DICHLOROISOCYANURATE	The material may cause severe skin irritation after prolonged or repeated exposure and may produce on contact skin redness, swelling, the production of vesicles, scaling and thickening of the skin. Repeated exposures may produce severe ulceration.
SODIUM CARBONATE & POLYPROPYLENE/ POLYETHYLENE GLYCOL COPOLYMER	The material may cause skin irritation after prolonged or repeated exposure and may produce on contact skin redness, swelling, the production of vesicles, scaling and thickening of the skin.

Acute Toxicity	✗	**Carcinogenicity**	✗
Skin Irritation/Corrosion	✓	**Reproductivity**	✗
Serious Eye Damage/Irritation	✓	**STOT - Single Exposure**	✗
Respiratory or Skin sensitisation	✗	**STOT - Repeated Exposure**	✗
Mutagenicity	✗	**Aspiration Hazard**	✗

Legend: ✗ *– Data either not available or does not fill the criteria for classification*
✓ *– Data available to make classification*

SECTION 12 ECOLOGICAL INFORMATION

Toxicity

Machine Dishwashing Powder

ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
Not Available	Not Available	Not Available	Not Available	Not Available

sodium carbonate

ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
LC50	96	Fish	300mg/L	4
EC50	48	Crustacea	=176mg/L	1
EC50	96	Algae or other aquatic plants	242mg/L	4
NOEC	16	Crustacea	424mg/L	4

sodium tripolyphosphate

ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
EC50	48	Crustacea	>100mg/L	2
EC50	96	Algae or other aquatic plants	69.2mg/L	2

polypropylene/ polyethylene glycol copolymer

ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
Not Available	Not Available	Not Available	Not Available	Not Available

sodium metasilicate, anhydrous

ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
LC50	96	Fish	2-320mg/L	2
EC50	48	Crustacea	1-700mg/L	2
EC50	72	Algae or other aquatic plants	207mg/L	2

sodium dichloroisocyanurate

ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
LC50	96	Fish	0.217mg/L	4
EC50	48	Crustacea	0.11mg/L	4
EC50	72	Algae or other aquatic plants	>100mg/L	2

Continued...

	EC90	3	Algae or other aquatic plants	0.5mg/L	2
	NOEC	96	Fish	0.056mg/L	2

Legend:	*Extracted from 1. IUCLID Toxicity Data 2. Europe ECHA Registered Substances - Ecotoxicological Information - Aquatic Toxicity 3. EPIWIN Suite V3.12 (QSAR) - Aquatic Toxicity Data (Estimated) 4. US EPA, Ecotox database - Aquatic Toxicity Data 5. ECETOC Aquatic Hazard Assessment Data 6. NITE (Japan) - Bioconcentration Data 7. METI (Japan) - Bioconcentration Data 8. Vendor Data*

On the basis of available evidence concerning either toxicity, persistence, potential to accumulate and or observed environmental fate and behaviour, the material may present a danger, immediate or long-term and /or delayed, to the structure and/ or functioning of natural ecosystems.
Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
Do NOT allow product to come in contact with surface waters or to intertidal areas below the mean high water mark. Do not contaminate water when cleaning equipment or disposing of equipment wash-waters.
Wastes resulting from use of the product must be disposed of on site or at approved waste sites.
For sodium carbonate
Environmental Fate:
As sodium carbonate has the capacity to drastically increase the pH of an ecosystm, the extent of its effect on organisms depends on the buffer capacity of the aquatic or terrestrial ecosystem, and the pH tolerance levels of the organisms living there. While the use of sodium carbonate could potentially result in its release into aquatic systems and cause an increase in pH, these levels are usually monitored in effluents, and can easily be corrected. If corrective measures are taken to control the pH of waste water no significant increase in the receiving water or adverse environmental effects is not expected with the use of sodium carbonate. The sodium ion will remain in solution and not adsorb to particulate matter. In water the carbonate ions will re-equilibrate until equilibrium is established, and will finally be incorporated into the inorganic and organic carbon cycle.
Ecotoxicity:
Aquatic invertebrate EC50 (48 h): Cladoceran ceriodaphnia cf Dubia: 200-227 mg/l (immobilisation).
The variation in acute toxicity for aquatic organisms may be explained by the variation in buffer capacity of the test medium. In general, mortality of the test organisms was found at concentrations higher than 100 mg/l, but for Amphipoda, salmon and trout, lethal effects were observed at 67- 80 mg/l.
For Chlorinated Isocyanurates:
Aquatic Fate: Chlorinated isocyanurates hydrolyze in water to form isocyanuric acid (cyanuric acid) and hypochlorous acid (HOCl). Hydrolysis products are responsible for acute aquatic toxicity. All of the chlorinated isocyanurates form hypochlorous acid when dissolved in water. Antimicrobial activity results from oxidation reactions with microbial enzyme systems. Isocyanuric acid and cyanuric acid remain and, under anaerobic conditions, degrade rapidly to carbon dioxide and ammonia.
Ecotoxicity: These products are likely to accumulate in mammals, fish and nontarget aquatic organisms. The chlorinated isocyanurates are practically nontoxic to birds; however, they are very highly toxic to cold water fish, highly toxic to warm water fish, highly toxic to freshwater invertebrates, and very highly toxic to estuarine and marine organisms.
For Phosphate: The principal problems of phosphate contamination of the environment relates to eutrophication processes in lakes and ponds. Phosphorus is an essential plant nutrient and is usually the limiting nutrient for blue-green algae.
Aquatic Fate: Lakes overloaded with phosphates is the primary catalyst for the rapid growth of algae in surface waters. Planktonic algae cause turbidity and flotation films. Shore algae cause ugly muddying, films and damage to reeds. Decay of these algae causes oxygen depletion in the deep water and shallow water near the shore. The process is self-perpetuating because an anoxic condition at the sediment/water interface causes the release of more adsorbed phosphates from the sediment. The growth of algae produces undesirable effects on the treatment of water for drinking purposes, on fisheries, and on the use of lakes for recreational purposes.
Prevent, by any means available, spillage from entering drains or water courses.
DO NOT discharge into sewer or waterways.

Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
sodium carbonate	LOW	LOW

Bioaccumulative potential

Ingredient	Bioaccumulation
sodium carbonate	LOW (LogKOW = -0.4605)

Mobility in soil

Ingredient	Mobility
sodium carbonate	HIGH (KOC = 1)

SECTION 13 DISPOSAL CONSIDERATIONS

Waste treatment methods

Product / Packaging disposal	▸ **DO NOT** allow wash water from cleaning or process equipment to enter drains. ▸ It may be necessary to collect all wash water for treatment before disposal. ▸ In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first. ▸ Where in doubt contact the responsible authority. ▸ Recycle wherever possible. ▸ Consult manufacturer for recycling options or consult local or regional waste management authority for disposal if no suitable treatment or disposal facility can be identified. ▸ Treat and neutralise at an approved treatment plant. ▸ Treatment should involve: Mixing or slurrying in water; Neutralisation with suitable dilute acid followed by: burial in a land-fill specifically licensed to accept chemical and / or pharmaceutical wastes or Incineration in a licensed apparatus (after admixture with suitable combustible material). ▸ Decontaminate empty containers. Observe all label safeguards until containers are cleaned and destroyed.

Ensure that the hazardous substance is disposed in accordance with the Hazardous Substances (Disposal) Notice 2017

Disposal Requirements

Packages that have been in direct contact with the hazardous substance must be only disposed if the hazardous substance was appropriately removed and cleaned out from the package. The package must be disposed according to the manufacturer's directions taking into account the material it is made of. Packages which hazardous content have been appropriately treated and removed may be recycled.
The hazardous substance must only be disposed if it has been treated by a method that changed the characteristics or composition of the substance and it is no longer hazardous.
Only dispose to the environment if a tolerable exposure limit has been set for the substance.
Only deposit the hazardous substance into or onto a landfill or sewage facility or incinerator, where the hazardous substance can be handled and treated appropriately.

Continued...

SECTION 14 TRANSPORT INFORMATION

Labels Required

	
Marine Pollutant	NO
HAZCHEM	2X

Land transport (UN)

UN number	1759
UN proper shipping name	CORROSIVE SOLID, N.O.S.
Transport hazard class(es)	Class: 8 Subrisk: Not Applicable
Packing group	III
Environmental hazard	Not Applicable
Special precautions for user	Special provisions: 223; 274 Limited quantity: 5 kg

Air transport (ICAO-IATA / DGR)

UN number	1759
UN proper shipping name	Corrosive solid, n.o.s. *
Transport hazard class(es)	ICAO/IATA Class: 8 ICAO / IATA Subrisk: Not Applicable ERG Code: 8L
Packing group	III
Environmental hazard	Not Applicable
Special precautions for user	Special provisions: A3 A803 Cargo Only Packing Instructions: 864 Cargo Only Maximum Qty / Pack: 100 kg Passenger and Cargo Packing Instructions: 860 Passenger and Cargo Maximum Qty / Pack: 25 kg Passenger and Cargo Limited Quantity Packing Instructions: Y845 Passenger and Cargo Limited Maximum Qty / Pack: 5 kg

Sea transport (IMDG-Code / GGVSee)

UN number	1759
UN proper shipping name	CORROSIVE SOLID, N.O.S.
Transport hazard class(es)	IMDG Class: 8 IMDG Subrisk: Not Applicable
Packing group	III
Environmental hazard	Not Applicable
Special precautions for user	EMS Number: F-A , S-B Special provisions: 223 274 Limited Quantities: 5 kg

Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

SECTION 15 REGULATORY INFORMATION

Safety, health and environmental regulations / legislation specific for the substance or mixture

This substance is to be managed using the conditions specified in an applicable Group Standard

HSR Number	Group Standard

Continued...

HSR2530	Cleaning Products (Subsidiary Hazard) Group Standard 2017

SODIUM CARBONATE IS FOUND ON THE FOLLOWING REGULATORY LISTS

GESAMP/EHS Composite List - GESAMP Hazard Profiles
IMO IBC Code Chapter 17: Summary of minimum requirements
IMO MARPOL (Annex II) - List of Noxious Liquid Substances Carried in Bulk
New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals
New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals - Classification Data
New Zealand Inventory of Chemicals (NZIoC)

SODIUM TRIPOLYPHOSPHATE IS FOUND ON THE FOLLOWING REGULATORY LISTS

GESAMP/EHS Composite List - GESAMP Hazard Profiles
New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals
New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals - Classification Data
New Zealand Inventory of Chemicals (NZIoC)

POLYPROPYLENE/ POLYETHYLENE GLYCOL COPOLYMER IS FOUND ON THE FOLLOWING REGULATORY LISTS

New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals
New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals - Classification Data
New Zealand Inventory of Chemicals (NZIoC)

SODIUM METASILICATE, ANHYDROUS IS FOUND ON THE FOLLOWING REGULATORY LISTS

International Air Transport Association (IATA) Dangerous Goods Regulations
International Maritime Dangerous Goods Requirements (IMDG Code)
New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals
New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals - Classification Data
New Zealand Inventory of Chemicals (NZIoC)
United Nations Recommendations on the Transport of Dangerous Goods Model Regulations

SODIUM DICHLOROISOCYANURATE IS FOUND ON THE FOLLOWING REGULATORY LISTS

International Air Transport Association (IATA) Dangerous Goods Regulations
International Maritime Dangerous Goods Requirements (IMDG Code)
New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals
New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals - Classification Data
New Zealand Inventory of Chemicals (NZIoC)
United Nations Recommendations on the Transport of Dangerous Goods Model Regulations

Hazardous Substance Location

Subject to the Health and Safety at Work (Hazardous Substances) Regulations 2017.

Hazard Class	Quantity beyond which controls apply for closed containers	Quantity beyond which controls apply when use occurring in open containers
Not Applicable	Not Applicable	Not Applicable

Certified Handler

Subject to Part 4 of the Health and Safety at Work (Hazardous Substances) Regulations 2017.

Class of substance	Quantities
Not Applicable	Not Applicable

Refer Group Standards for further information

Tracking Requirements

Not Applicable

National Inventory Status

National Inventory	Status
Australia - AICS	Yes
Canada - DSL	Yes
Canada - NDSL	No (sodium tripolyphosphate; polypropylene/ polyethylene glycol copolymer; sodium metasilicate, anhydrous; sodium dichloroisocyanurate; sodium carbonate)

Continued...

China - IECSC	Yes
Europe - EINEC / ELINCS / NLP	No (polypropylene/ polyethylene glycol copolymer)
Japan - ENCS	Yes
Korea - KECI	Yes
New Zealand - NZIoC	Yes
Philippines - PICCS	Yes
USA - TSCA	Yes
Taiwan - TCSI	Yes
Mexico - INSQ	No (polypropylene/ polyethylene glycol copolymer)
Vietnam - NCI	Yes
Russia - ARIPS	Yes
Legend:	*Yes = All CAS declared ingredients are on the inventory* *No = One or more of the CAS listed ingredients are not on the inventory and are not exempt from listing(see specific ingredients in brackets)*

SECTION 16 OTHER INFORMATION

Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.
The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

Definitions and abbreviations

PC—TWA: Permissible Concentration-Time Weighted Average
PC—STEL: Permissible Concentration-Short Term Exposure Limit
IARC: International Agency for Research on Cancer
ACGIH: American Conference of Governmental Industrial Hygienists
STEL: Short Term Exposure Limit
TEEL: Temporary Emergency Exposure Limit。
IDLH: Immediately Dangerous to Life or Health Concentrations
OSF: Odour Safety Factor
NOAEL :No Observed Adverse Effect Level
LOAEL: Lowest Observed Adverse Effect Level
TLV: Threshold Limit Value
LOD: Limit Of Detection
OTV: Odour Threshold Value
BCF: BioConcentration Factors
BEI: Biological Exposure Index

Powered by AuthorITe, from Chemwatch.